

WATERPROOF IP69K WASHDOWN BARLIGHTS

FOR FOOD, BEVERAGE & PHARMACEUTICAL MACHINE VISION APPLICATIONS:

- Pick & Place robotics
- Product, packaging & label inspection
- Foreign object detection

- Manufacturing Process Control
- Aseptic manufacturing





IP69K WASHDOWN LIGHTS

are so much more than a light in a waterproof casing! Read our Tech Note to understand WHY you may need a TPL Vision IP69K Washdown light.











LIGHTING METHODS







DIRECT


DARKFIELD

LINE SCAN

SUITABLE FOR HARSH FOOD & CHEMICAL ENVIRONMENTS.

Backlight version available: see Waterproof IP69K Washdown Backlight Bars.

LIGHTING AREA




Data shown for white light

TECHNICAL DATA

Operating voltage	24 VDC					
Supplied cable length	5 meters					
Operating modes	Continuous and Strobe					
Trigger (strobe) mode	PNP & NPN					
Rise time / Fall time	15 μs / 10 μs					
Dimming control	Yes, 100% - 35%					
Ambient temperature	-20°C to +60°C (-4°F to +140°F)**					
Ambient humidity	80% max					
IP rating	IP69K (IEC 60529)					
Housing	316L stainless steel / food grade PPMA					
L-Brackets (included)	Design permits 360° rotation of light					
Warranty	3 years (UV: 1 year) * See www.tpl-vision.com/warranty					
COLOURS: UV 405	WHI 470 525 630 IR 850					
DIFFUSER OPTIONS	OPAQUE SATIN POLARISED to remove reflections					

^{**} See Technical User Guide

SIZE OPTIONS



TPL Vision has the best solutions for IP69K lights on the market.

We searched the world and have tried many different lights, but nothing comes close to TPL's quality.

They have helped us surpass the industry standard and have taken our product to the next level. ? ?

Jeff Youngs, President and CEO, ProSpection Solutions, LLC



EBAR

(cm)
125
250
375
500
625
750
875
1000
1125
1250


LENGTH (cm)	(nm or WHI)	П	LENS TYPE		ENCLOSURE RATING	-	DIFFUSER AND POLARISER OPTION		
125	WHI	7	(±7°)		IP69K		DO	(opaque)	
250	405	1	0 (±10°)				DS	(satin)	
375	470	9)- 16 (±9-16°)				POL	(polariser)	
500	525	1	. 7 (±17°)				(leave blank	for clear window)	
625	630	2	!5 (±25°)				Note: cannot be fitted retro- spectively, must be specified		
750	850	N	(no lens)				at time of order.		
875							Polariser nowith 850nm	t suitable for use	
1000								,	
1125	EXAMPLES:								

• EBAR+ IP69K 125mm white LED ±7° lenses transparent diffuser ⇒ EBAR-125-WHI-7-IP69K • EBAR+ IP69K 500mm green LED ±17° lenses opaque diffuser

→ EBAR-500-525-17-IP69K-D0

CABLE

STRAIGHT M12 5P EXTENSION CABLE



ACCESSORY

SAFETY GLASSES



LOAN EQUIPMENT

Loan equipment is available for evaluation.

Please contact your TPL Vision Sales Executive for more information:

contact@tpl-vision.co.uk

Ref.TS-070301-A1, 06/2020 Edition.

CCTPL Vision is a true partner. TPL provides outstanding service and support. We have found their responsiveness to be unmatched in the industry. ??

Jeff Youngs, President and CEO, ProSpection Solutions, LLC



PHONE +44 (0)1738 310 392

EMAIL contact@tpl-vision.co.uk

www.tpl-vision.com



www.rjwilson.com sales@rjwilson.com 781-335-5500